

PAINTING

- **PLASTER:** New masonry surfaces refer to the MSDS for A must be allowed to wher gives detailed informati completely. It is r h o m e n g e t h e o p a i n t , w h i c h i s a allow 28 days as t h s t o e i n g e t c o n t a i n e r w i t h t h e l for new masonry surface position, in a cool, d
- **CLEANING:** Surface should be out of reach of children free from any loose material, dust, oil, grease. Growths of fungus or moss should be removed by wire brushing and water. When in contact immediately with the underlying surface. Seek medical advice. Chalkiness, in spite of surface cleaning, used plenty of water. Get medical advice if it persists.
- **FILLING FOR CRACKS:** For filling cracks upto 3mm use a suitable pad during sanding. SmartCare Crack Seal to avoid dust inhalation.
- **FILLING FOR HOLES & DENTS:** In case of dents and holes use Asian Paints Wall Putty or a mixture of white cement and fine sand in the ratio 1:3.

For the best performance of washing of the painting surface and fungal growth, if any, a months.

- Do not apply when ambient temperature is less than 10°C or application.
- Do not over-thin or over-extend the brush.
- Tint using Asian Paints machine colourants only and Stir
- For extremely rough surface: Application by brush is recommended.
- Paint will not cover existing cracks, proper care to be taken.
- For surfaces having heavy algal infestation, proper cleaning should be ensured.
- Primer coat or only one coat of topcoat should not be kept.
- Specially in pre-monsoon season, horizontal surface to be marked of algal growth if any.
- For best performance ensure that the surface is dry. On m Red zone, find out the source of water and address it before Care Primo recommended.
- Thinned paint should be consumed within 24 hours of dilution. Post 24 hours thinned paint may