

PAINTING

- **PLASTER:** New masonry surfaces refer to the MSDS for A must be allowed to wher gives detailed informati completely. It is r h o m e n g e t h e o p a i n t , w h i c h i s a allow 28 days as t h s t o e i n g e t c o n t a i n e r w i t h t h e l for new masonry surface position, in a cool, d
- **CLEANING:** Surface should be out of reach of children free from any loose s p a g e , h a d m f u b r i f s w a l l o w e d . I grease. Growths of f m m g d a t a l m e d i c a l a t t e n t i o n . or moss should be r w o v e d e y e p r o t e c t i o n d u r i n g a p p by wire brushing and w i w a t e r e y e w h e n i n s e i m m e d i a t e l y w the underlying surface e e k e m a d b c a b a d v i c e . chalkiness, in spi e n o f a s h o o b u g k i n c o n t a c t i m m e d i surface cleaning, use d A p l a n t y o f w a t e r . G e t m e d i c Paints SmartCare Primer e b o p s o r p e r s i s t s .
- **FILLING FOR CRACKS:** For fill b D o n o t b r e a t h e v a p o u r o r s p r a y cracks upto 3mm use A s t a b l e p a n o s e p a d d u r i n g s a n d i SmartCare Crack Seal to avoid dust inhalation.
- **FILLING FOR HOLES & DENTS:** In • D o n o t p o u r l e f t o v e r p a i n t d o w case of dents and h o b e s s e A s i a n Paints Wall Putty • r n a t h e x e v e n t o f s p i l l s , c o n t a i white cement and fine sand in theratio 1: 3.

For the best performance of washing of the painting surface and fungal growth, if any, a months.

- Do not apply when ambient temperature is less than 10°C o application.
- Do not over-thin or over-extend the brush.
- Tint using Asian Paints machine colourants only and Stir
- For extremely rough surface: Application by brush is reco
- Paint will not cover existing cracks, proper care to be t applied.
- For surfaces having heavy algal infestation, proper clean
- Primer coat or only one coat of topcoat should not be kep be ensured.
- Specially in pre-monsoon season, horizontal surface to be marks of algal growth if any.
- For best performance ensure that the surface is dry. On m Red zone, find out the source of water and address it bef Care Primo recommended.
- Thinned paint should be consumed within 24 hours of dilut necessary amount of paint. Post 24 hours thinned paint ma